

Jefferson 10000 Lumens Rechargeable COB LED Torch JEFTRCH33

Specification

Charging performance:

Battery: 2 x 20650 7.4V-2600mAh 5w
Charging current: 1.5A
Charging time: 5hrs
Charging port: Type-c

Full power indicator:

Green light on.

Discharge performance

Switch modes: High-Mid-Low-off
Quick press twice Strobe, press and hold boost.

Discharge method

Reduction voltage, Curve drop.
Quiescent Dissipation: <60µA
Low power warning: Red light on

Special function:

Power bank output: 5V2A

Size: 55.6 x 33 x 242.5mm **Weight:** 450g battery included

Drop test: 1M 6 time **Waterproof:** IP67



Brightness and Runtime

Switch mode:	Boost	High	Mid	Low
Brightness:	10000lm	5000lm	3000lm	700lm
Run time:	30sec	1.5hrs	2hrs	4hrs
LUX (2m):	2500	600	280	160
Beam distance:	200	100	65	50
CRI:	>70			
Colour Temperature:	6000-7000k			
Beam Angle:	50degrees			

**HYPER
BEAM**

Declaration Of Conformity

We, Jefferson Professional Tools & Equipment, as the authorised European & UK representative of the manufacturer, declare that this equipment conforms to the requirements of the following:

CE: EN IEC 55015:2019+A11:2020 EN61547:2009 EN IEC 61000-3-2:2019+A1:2021 EN 6100-3-3:2013+A2:2021+AC:2022

UKCA: BS EN IEC 55015:2019+A11:2020 BS EN61547:2009 BS EN IEC 61000-3-2:2019+A1:2021 BS EN 6100-3-3:2013+A2:2021+AC:2022

Notified Testing Body: SHENZHEN TIMEWAY TESTING LABORATORIES. Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road, West, Tong Le Village, Nanshan District, Shenzhen, China

Signed: Stephen McIntyre
Operations Manager

Name and address of manufacturer:

Jefferson Professional Tools & Equipment 24 Lisgorgan Lane, Upperlands, BT46 5TE Tel: +44 (0)1244 646 048 (UK) +353 (0)1473 0300 (ROI) Email: info@jeffersonstools.com