



15A BATTERY CHARGER 12V-24V (20A 300SEC BOOSTER)

JEFBATCHG15-1224

- Designed for charging all types of 12V and 24V lead-acid batteries including; Wet (Flooded), Gel, MF (Maintenance-Free), CA (Calcium), EFB (Enhanced Flooded Battery), and AGM (Absorption Glass Mat) batteries
- Suitable for charging battery capacities from 2 to 400Ah (12V),
- 50 to 400Ah (24V) and maintaining all battery sizes
- Supplied with 1.7 meter DC and 0.5 meter battery clamp connectors
- 20A booster enables a fast charge within 300 seconds
- Output:
 - Voltage: 12V DC / 24V DC
 - Current: 12V DC - 2A / 4A / 6A / 8A / 10A / 15A or 24V DC - 3.5A/7.5A or 12V DC - 20A (300 seconds boost charge)
- Input:
 - Voltage: 220-240V AC ~ 50Hz
 - Current: 2.5A
- Temperature controlled
- Weight: 1.7Kg
- Max Rated Capacity: 2 - 400Ah (12V)
- Power: Max. 350W
- Weight: 1.7Kg
- IP Rating: IP20



Jefferson®
PROFESSIONAL TOOLS & EQUIPMENT