



# DYNAMO 30A BATTERY CHARGER

JEFBTRYCHG030

This battery charger is designed for lead accumulators on petrol and diesel engines, motor cycles, boats etc. The charging current delivered by the battery decreases according to the characteristic W bend - see the DIN 41774 norm. The battery case has an IP20 protection rating against indirect contacts by an earth lead as specified for Class 1 equipment. Please ensure that the appropriate mains voltage is available before use and ensure that the plug has an earth connection.

- Input Voltage: 230V ~ 50Hz
- Input Power: 40 W
- Output Voltage: 12V / 24V
- Output Charge Peak(EN): 30A (25A)
- Battery Capacity (Min - Max): 3 - 320Ah
- Duty Cycle: 5 sec ON / 30 sec OFF @ 5 Cycles
- Charging Rates: 2
- Fast Charge Timer: No
- Fuse: 1 x 20A / 1 x 5A
- Ingress Protection Rating: IP21
- Charging cables: 2.5mm x 2M with fully insulated charging clamps
- Power Cable: 3x1.0mm x 2M
- Plug: 3A
- Weight: 4.8kg
- Dimensions: 235 x 195 x 190mm



**Jefferson**<sup>®</sup>  
PROFESSIONAL TOOLS & EQUIPMENT