

DIGITAL TYRE INFLATOR

JEFGTYJTPC10D

- Die cast aluminium body
- High contrast large backlit LCD screen for easy viewing in any light condition
- Auto on upon air pressure sensing
- One button operation with pressed operating lever: full press to inflate, halfway to deflate, release to measure pressure
- Low battery alert
- Four pressure settings: psi, bar, kPa, kg/f
- Hose Length: 0.5m
- Tyre Valve Connection:
Twin push on/hold on
- Air Supply Connection: 1/4" Female BSP Thread - 1/4" Male (Quick Release)
- Max. Inlet Pressure: 15bar
- Tyre Pressure Range:
0.5 - 12bar
7 - 174psi
50 - 1200kPa
0.5 - 12kg/f
- Flow Rate: 900L/min @ 12bar
- Lithium-ion battery
- 0.8m USB-C charging cable included
- Max. Run Time: 40 hours
- Max. Charge: 2.5 hours
- Weight: 1.09kg
- Dimensions: 360 x 140 x 100mm




BARCODE

5060813458080

SWIVEL DIAL TYRE INFLATOR

JEFGTYLCLC09

- Display head can be rotated 360°
- Two unit pressure gauge: psi, bar
- One lever operation
- Durable rubber sleeve
- Hose Length: 0.5m
- Air Supply Connection: 1/4" Female BSP Thread - 1/4" Male (Quick Release)
- Max. Inlet Pressure: 15bar
- Tyre Pressure Range:
0.5 - 12bar
7 - 180psi
- Flow Rate: 500L/min @ 174psi
- Weight: 1.04kg
- Dimensions: 373 x 141 x 46mm



BARCODE

5060813458097