



DYNAMO JUMP STARTERS

JEFJMPSTA500 JEFJMPSTA1000

- Heavy-duty steel case, high power US manufactured battery and industrial quality switchgear make this model suitable for starting most vehicles
- Easy-to-read LED battery indicator to IEC 51 provides fast indication of battery's state of charge
- Surge and spike suppressing circuitry reduces risk of damaging vehicle's on-board electronics
- Fitted with charge balance circuitry to provide even charge to integral batteries
- Supplied with mains voltage recharge unit



SPECIFICATION

Horse Power	500HP	1000HP
Voltage	12/24V	12/24V
Charger 230v	12 Volt 5 Amp	12 Volt 5 Amp
Peak Amps 12v	4400A	7000A
Peak Amps 24v	2200A	3500A
Cranking Current (20°C, 5 Secs) 12V	1700A	1900A
Cranking Current (20°C, 5 Secs) 24V	850A	950A
Cold Cranking Current (18°C, 5 Secs) 12V	700A	800A
Cold Cranking Current (18°C, 5 Secs) 24V	350A	400A
Cable Section	35mm2	35mm2
Cable & Clamp Length	2m	2m

Jefferson[®]
PROFESSIONAL TOOLS & EQUIPMENT

www.jeffersonstools.com



UK: +44(0) 1244 646 048 | ROI: +353(0) 1473 0300