



1100W SUBMERSIBLE SEWAGE PUMP

JEFSUBPISEW270-10

JEFSUBPISEW270-10-110

SUITABLE APPLICATIONS INCLUDE:
CONSTRUCTION SITES
AGRICULTURAL ENVIRONMENTS
COMMERCIAL ENVIRONMENTS

- An industrial submersible pump with a high-speed vortex impeller, rotary cutter and float switch designed for processing and draining sewage
- Manufactured from corrosion resistant materials with aluminium motor case
- Designed for pumping sewage and dirty water with a maximum flow rate of 270L/min
- 2" discharge hose connector
- 10m maximum head
- Rated Power / Motor: 1100W
- Power Supply: 110V / 230V ~ 50Hz
- Maximum Flow Rate: 270L/min / 16200 L/hr
- Maximum Head: 10m
- Maximum Depth: 5m
- Maximum Viscosity: $7 \times 10^{-7} - 23 \times 10^{-6} \text{ m}^2/\text{s}$
- Maximum Density: $1.2 \times 103 \text{ kg/m}^3$
- Maximum Temperature: 40°C
- Cable Length: 10m
- Insulation Class: B
- Ingress Protection: IP68
- Outlet Diameter: 2"
- Dimensions: 245 x 200 x 477mm
- Weight: 23kg



2" OUTLET / DISCHARGE HOSE CONNECTION INCLUDED



MOTOR CASING

CARRY HANDLE

FLOAT SWITCH

2" OUTLET / DISCHARGE HOSE CONNECTION

CUTTER



Jefferson[®]
PROFESSIONAL TOOLS & EQUIPMENT