



# TUNDRA 50HP SCREW COMPRESSOR 10 BAR 415V

**TUNCINDSPMVS-50.0**

- Permanent magnet oil cooled variable speed direct driven screw compressor
  - Fitted with an efficient heavy duty three-phase electric motor (IE4)
  - Low noise levels with sound levels measured at 70dB(a) from a 1.5 meter distance
  - 96% efficiency at full load
  - 100% duty cycle application
  - Discharge air connection: 1-1.5"
  - Dimensions: 1300mm (L) x 1000mm (W) x 1210mm (H)
  - Weight: 505kg
- 
- Voltage: 3 Phase (50A)
  - Power: 50HP / 37kW
  - Input Current: 90A
  - Motor Speed: 3000rpm
  - Max Pressure: 10Bar / 145psi
  - Free Air Delivery: 209cfm / 5.9m<sup>3</sup>/min @ 10Bar

## COMPATIBLE WITH



1 LITRE HT68  
COMPRESSOR OIL

**JEFOILHT68-1L**

**DRIER TANKS FROM  
500-1000L AVAILABLE  
ON REQUEST**



**LOW NOISE OUTPUT**



**3-Phase**

**90  
AMP**

**37  
kW**

**Direct Drive**

**100%  
DUTY CYCLE**

**INDUSTRIAL**

**Jefferson®**  
PROFESSIONAL TOOLS & EQUIPMENT

[www.jeffersonstools.com](http://www.jeffersonstools.com)



UK: +44(0) 1244 646 048 | ROI: +353(0) 1473 0300