

TUNDRA 3/4" DEEP IMPACT SOCKETS

- Dual hole configuration and ring groove for effortless attachment and removal
- Manufactured from Chrome Molybdenum steel for extreme impact durability
- 6-Point gripping for best fit and exceptional durability and lasting performance in high-torque applications
- Laser etched part numbers
- Suitable for use on all types of impact tools
- Non-slip hex geometry prevents socket and fastener rounding
- Square drive



| BARCODE | PRODUCT | SIZE | WEIGHT(KG) | DIMENSIONS |
|---------------|---------------|------|------------|-----------------|
| 5060813456611 | TUNISCI34-24D | 24mm | 0.6 | 155 x 52 x 38mm |
| 5060813456628 | TUNISCI34-27D | 27mm | 0.625 | 155 x 52 x 41mm |
| 5060813456635 | TUNISCI34-30D | 30mm | 0.705 | 155 x 52 x 46mm |
| 5060813456642 | TUNISCI34-32D | 32mm | 0.745 | 155 x 52 x 48mm |
| 5060813456659 | TUNISCI34-36D | 36mm | 0.84 | 155 x 53 x 53mm |
| 5060813456666 | TUNISCI34-41D | 41mm | 1.01 | 155 x 59 x 59mm |
| 5060813456673 | TUNISCI34-46D | 46mm | 1.2 | 155 x 65 x 65mm |



INDUSTRIAL

DIN 3121

Cr-Mo
chromoly

ISO1174-2